

Description

Purekor FSC Certified Fire Retardant Lumber is a high quality fire retardant product that is ideally suited where building code requires fire retardant lumber for LEED rated construction projects.

LEED Credits

MR 5.1 + 5.2 (location dependent)
MR 7.0

Uses

Purekor FSC Fire Retardant Lumber is ideal where building code applications require the use of fire treated lumber that is also FSC Certified.

Product Features

Multiple LEED Credits:

Contributes to multiple LEED Credits simultaneously

FSC Certified:

Contains 100% FSC Certified Fiber

Class A Fire Retardant

High quality Western Hem Fir raw material

Kiln Dried After Treatment (KDAT)

Service

Panel Source International can provide you with all your green forest product needs. Our product experts are available to answer any questions you may have regarding this product or any other, as well as LEED® requirements.

Species and Grades Available:

All Purekor FSC Certified Fire Retardant Lumber is produced from kiln dried Western Hem Fir. Specifications include the following:

Grades: Panel Source stocks 2x4 fire retardant in both Std&Btr and 2&Btr Grades. For 2x6, 2x8, 2x10, and 2x12 Panel Source stocks this material in 2&Btr Grades. Alternate grades include the following:

#3 Common, #1 Structural Light Framing, Select Structural

After treatment the lumber is kiln dried to a maximum of 15% moisture content.

All lumber is graded under American Lumber Standards by the Western Wood Products Association, (WWPA) and all graded lumber is stamped with the appropriate grade, the mill number, and the certifying agency.

All lumber is surfaced four sides (S4S), eased edges (E/E) and double end trimmed (DET)

Product Selection:

Panel Source maintains a large inventory of this product for prompt shipment. This inventory includes the following dimensions and lengths:

2x4: Even lengths from 8'-20' and Precut 8' and 10' studs

2x6: Even lengths from 8'-20' and Precut 8' and 10' studs

2x8: Even lengths from 8'-24'

2x10: Even lengths from 8'-24'

2x12: Even lengths from 8'-24'

Panel Source can also supply you with a complete selection of fire retardant timbers from 4x4 to 12x12 in lengths from 8' to 40'.

Purekor® and Pyroblock® are registered trademarks of Panel Source International, Inc.

