



Section 1 - Chemical Product

Product/Chemical Name: Pyroblock Platinum Veneer Core Plywood

Overview

Section 2 - Composition / Information on Ingredients

Component:	Exposure Limit (OSHA)
Softwood Dust	10mg/m ³ PEL 5mg/m ³ ACGIH TLV-TWA
Melamine 108-78-1	N/A
Phenol-Formaldehyde Trace	0.75ppm 2ppm STEL

Section 3 - Physical and Chemical Properties

Physical State: Solid

Appearance and Odor: light yellow to light brown
with light wood odor

Specific Gravity: <1

pH: N/A

Solubility: N/A

Solubilities: N/A

Boiling Point: N/A

Freezing/Melting Point: N/A

Section 4 - Fire-Fighting Measures

Flash Point: N/A

Autoignition Temperature: N/A will be dependent on exposure to heat and other variables.

Extinguishing Media: Water, Carbon Dioxide, Sand

Unusual Fire and Explosion Hazards: Sawing, sanding or machining can produce wood dust as a by product which may present an explosion hazards. An airborne concentration of 40 grams or dust per cubic meter of air is often the LEL for wood dust.

Fire-Fighting Equipment: Because fire may produce toxic products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Section 5 - Stability and Reactivity

Stability: Pyroblock FSC Certified Plywood is stable at room temperature in normal storage and handling conditions.

Conditions to Avoid: Keep away from heat, sparks, and open flames.



Panel Source – A Division of McKillican International, Inc.

www.mckillican.com

www.panelsource.net



Hazardous Decomposition Products: Thermal decomposition can produce irritating and toxic fumes, and gases.

Section 6 - Health Hazard Information

Potential Health Effects

Inhalation: Inhalation may result in respiratory irritation and coughing.

Eye: Contact with the eyes may cause irritation

Skin: Contact with the skin may cause irritation

Ingestion: Not likely to happen

Carcinogenicity Listing: IARC, NTP and OSHA-Formaldehyde a possible human carcinogen, IARC Group 2a.

Formaldehyde off-gas levels based on ASTM E-133 have shown an average concentration of 0.09ppm with a standard deviation of 0.04. NTP known to be a human carcinogen (10th report), IARC Monographs: Wood Dust, Group 1-IARC Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity.

Emergency and First Aid Procedures

Inhalation: Remove to fresh air. If irritation persists, get medical attention.

Eye Contact: Flush eyes with water for at least 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and shoes. Wash exposed areas with soap and water. Call a physician if irritation persists.

Ingestion: Call a physician immediately. Only induce vomiting if directed by a physician. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Do not give anything by mouth to an unconscious person.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Section 7 - Special Precautions and Comments

Handling Precautions: Like any sawdust, avoid breathing product dust. Do not take internally. Wash thoroughly after handling this material.

Storage Requirements: Keep product unitized until use. Keep away from moisture, humidity, temperature extremes, heat, sparks, and open flames.

Revision Notes: V 3.0 modified 07/31/07, original 9/18/03

Disclaimer: This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Panel Source. The data on this sheet relates only to the specific material designated herein. Panel Source International assumes no legal responsibility for use or reliance upon these data.



Panel Source – A Division of McKillican International, Inc.

www.mckillican.com

www.panelsource.net