

PUREKÖR™ FSC Platinum Sheathing Plywood

Description:

Purekor Platinum Sheathing Plywood is an industrial grade Fir plywood panel that contains no added Urea Formaldehyde and uses 100% FSC Certified fiber.

LEED Credits:

MR 5.1 + 5.2 (location dependent)
MR 7.0
EQ 4.4

Uses:

Purekor Platinum Sheathing Plywood is manufactured for use in roof, flooring or wall sheathing applications.

Product Features:

Multiple LEED Credits:

Contributes to multiple LEED Credits simultaneously

FSC Certified:

Contains 100% FSC Certified Fiber

Available in the following grades:

CD, CC, CC P+TS, AC and Struc-1

Complete selection of thicknesses:

Available in 3/8", 15/32", 19/32", 23/32", 31/32", 1-1/8"

Available as Class A Fire Retardant:

See Purekor Fire Retardant Plywood

Service:

McKillican can provide you with all your green forest product needs. Our product experts are available to answer any questions you may have regarding this product or any other, as well as LEED® requirements.



Specifications:

Purekor Platinum Sheathing Plywood is made with no added urea formaldehyde. This product contains 100% FSC Certified Content and is certified under Panel Source Chain of Custody number SCS-COC-001034. Purekor Platinum Sheathing Plywood is produced under Performance Standard PS-1 and is certified by the American Plywood Association. The panel is available as CC, CD, CC P+TS, AC and Struc-1.

Sizes/Thicknesses:

Thicknesses	3/8", 15/32", 19/32", 23/32", 31/32", 1-1/8"
Finished Mat Size	48"X96"
Thickness Tolerance	+/- .005"
Length/Width Tolerance	+/- 1/32" per lineal foot

Physical Properties:

Modulus of Rupture	4757 psi	(32.8 N/mm ²)
Modulus of Elasticity	561,000 psi	(3998 N/mm ²)
Hardness	500 lbs	(2222 N)
Screw Hold (face)	371 lbs	(1645 N)
Density	34lbs / cu ft	(540kg/M ³)



Panel Source – A Division of McKillican International, Inc.

www.mckillican.com

www.panelsource.net

Green Building Information Center: 1-877-464-7246